

BRUHAT BANGALORE MAHANAGARA PALIKE						
NAME OF WORK : GRANTS OF INFRASTRUCTURE UP GRADATION OF YELAHANKA GOVT HOSPITAL						
CLIENT: YELAHANKA GOVERNMENT HOSPITAL						
MATERIAL RECEIVED SIGNATURE COPY FROM CLIENT						
SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
1	1	VVIP Executive Chair – : Fire retardant breathable mesh for backrest and Polyester fabric for seat. Black colour on seat and back (TW 182 Mesh & 5060 fabric seat) Base : 700 mm diameter raised Nylon base with 60 mm castors for stability and easy movement . Seat cover : Casement cloth protection for seat understructure, Adjustable Arms : Moves up or down for shoulder and upper body support. The firm polyurethane arm pads adjust vertically to accommodate different arm lengths from the shoulder to the elbow (TSA012 – value lab pad), Lumbar Support: "S" shaped backrest follow's the natural curve of the back for lower back support. Additional support by static polypropylene lumbar pad on back rest . Seat Contour : Seat pan depth is designed so that the forward most point on the lumbar support is placing gentle pressure on the lower 5 vertebrae on the spine. (2018 – Nuclear Seat), Synchro tilt with single lock : Chair Back reclines synchronously to a 2-to-1 ratio to seat angle. Allows user to recline while keeping seat cushion relatively level to floor. Use the tilt lock for upright posture like keyboarding. Pneumatic height : Change the height of the chair relative to the floor by 100 mm . Headrest : Fixed head rest for neck support	NO	3.00	3.00	12/27/2021
2	2	Doctor's Executive Chair : 1. High back chair with head support. 2. The double mesh back should be designed for comfort and support. 3. Adjustable seat height, head rest height & Hand rest angle, 4. Adjust the height using the gas lift to find that comfortable position, and the nylon castors make it easy to move around your space, 5. Five-part Chrome legs, 6. Height 48" + 2", 7. Width 26" + 2", 8. Depth 20" + 2" <u>Should be ISI / CE certified</u>	NO	10.00	10.00	12/27/2021
3	4	Steel Racks: 1. Steel rack made of slotted angles of size 2"x2"x3mm thick, 2. 5 compartments of six 6' x 1 1/4' x 3' length. 3. Paint: Epoxy powder coated in seamen's Gray Colour with minimum 50 microns 4. Should be ISI / CE Certified	NO	12.00	12.00	1/22/2022
4	5	Patient Cots (Plain):1. Size-78"Lx36"Wx24"H, 1 1/4" dia 14 SWG tubular Head and leg bows ERW Tube.2. The head bow and leg bows are 42" and 36" Height respectively. Head and leg bows are 14 gauge, 1" dia ERW cross bar and 1/2" dia 16-gauge ERW three vertical support bars.3. Top Sheet 18 SWG CRCA Sheet, double Press bent uniformly on all the four sides, 2" vertically and 3/4" further inside. A 6" broad x 2" deep full length 16-gauge square cross section rib is reinforced to the top sheet 2 Nos. M.S. Gages using 10 SWG. 4. Zinc plated 1/2" nuts & bolts, 4 Nos. of Shoes made up of white nylon are provided. 5. Epoxy powder coated with seamen's Gray Colour with 50 microns minimum coating.	NO	10.00	10.00	1/22/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
5	6	Patient Cots with side railings: 1. Efficient Height adjustable, manually operated, two section cots with perforated top. 2. The size of approximately 84" length, 36" width and an approximate height adjustable from 20" to 33" with $\pm 5\%$ tolerance 3. The head bow and leg bows are 42" and 36" Height respectively. Head and leg bows are 14 gauge, 1" dia ERW cross bar and $\frac{1}{2}$ " dia 16-gauge ERW three vertical support bars. 4. Having a Trendelenburg and reverse Trendelenburg movements. 5. Detachable and collapsible Sturdy railing, made of stainless steel of minimum 25mm diameter and 16-gauge tubes Capsule tubular frame, with a locking facility for raised position.	NO	3.00	3.00	2/2/2022
6	7	Computer Tables and Chairs for Departments excluding e-hospital: Legs : Durable steel powder coated under structure (Broken White) Accessories : Two Wire management holes at either ends of the table to access your cables. Multipurpose & Convenient : table can be kept in your office as well as your home. Its functional design allows you to use this table as a study desk, computer desk, writing table etc. Chair Material : Fire retardant breathable mesh for backrest and Polyester fabric for seat. Black colour on seat and back (TW 182 Mesh & 5060 fabric seat) Base : 700 mm diameter Nylon base with 50 mm castors for stability and easy movement . Seat cover : Injection moulded polypropylene seat edge and understructure protection .Adjustable Arms : Moves up or down for shoulder and upper body support. The firm polyurethane arm pads adjust vertically to accommodate different arm lengths from the shoulder to the elbow (TSA012 - value lab pad) Seat Contour : Seat pan depth is designed so that the forward most point on the lumbar support is placing gentle pressure on the lower 5 vertebrae on the spine. (2018 - Nuclear Seat) Lumbar Support : Soft but firm polyurethane lumbar support easily adjusts to support your lower back just where you feel it is needed .Synchro tilt with single lock : Chair Back reclines ynchronously to a 2-to-1 ratio to seat angle. Allows user to recline while keeping seat cushion relatively level to floor. Use the tilt lock for upright posture like keyboarding . Pneumatic height : Change the height of the	NO	30.00	30.00	12/27/2021
7	10	Drugs Transport Trolleys: 1. Trolley with 25 mm diameter SS tubular frame 2. Drawers 6 number possible of adequate size with top flat stainless steel 3. Size - 36-inch L x 20-inch W x 60-inch H. 4. 1 rows of hand out bins of different size & colour to hold different sizes 5. Light weight plastic box with drawers of different sizes and colours to hold emergency drugs 6. Facility to carry monitor and Defibrillator with Stainless steel saline rod-one. 7. Nylon Castor wheels of 12.5 cm dia- Two having locking arrangement.	NO	3.00	3.00	12/30/2021
8	11	3 Bucket System (Mopping): Material Stainless Steel Applications Mopping system, Bucket Capacity 30-60 L, 48 Lt. Trolley Material Stainless Steel, Model APC-119/3SS Number of Buckets 3, Usage/Application Hospitals, Brand Amsse Color Red Down Press Wringer yes	NO	2.00	2.00	2/14/2022
9	12	Fibre Pallets (Pharmacy) MainStore : Fiber Pallets 4"x 5"	NO	20.00	20.00	2/14/2022
10	14	Cushion Chair with Arm: Brand Maruthi, Color option available' Seat Material Fabric, Size standard, Design Type Customized, No Of Wheels 5, Revolving Chair Yes Material cushion, Condition New, Minimum Order Quantity 1 Piece	NO	20.00	20.00	2/1/2022

SL No	Item no	
11	15	BI G N R V
12	17	
13	18	
14	21	
15	22	
16		
17		

Sl. No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
11	15	Blood Drawing Chair: Color Blue, Material Stainless steel General Use Blood banks, Brand Agile Number Of Seats 1, Weight 120 kg, Automation Grade Remote Controlled, Usage/Application Hospitals, Blood Banks, Voltage 220 V	NO	2.00	2.00	1/22/2022
12	17	Plastic Chair: 1. Should be made from the finest polypropylene. 2. Should be Tough and lightweight. 3. Should be Good quality and Modern designed. 4. Should be Weatherproof and virtually maintenance free.	NO	100.00	100.00	12/27/2021
13	18	Wooden Tables with Drawers: Surface Finish Polished Material Particleboard, Size 4x2 Feet Shape Rectangular, Warranty 1 Year Seating Capacity 1 Seater	NO	20.00	20.00	12/29/2021
14	21	Folding Cots Material: Steel Pipe, Capacity: 120 kg	NO	10.00	10.00	2/1/2022
15	22	Almirah: Steel: 1. Size: 78" x 36" x 19" with 3 Shelves to be fixed having 4 compartments. 2. 1 compartment with Locker having lever lock placed in a suitable place. The locking system must be mounted securely to give robustness and long life. 3. Double door with three way locking device with duplicate keys, made out of CRCA Sheet of 18 gauge with de-rusted synthetic enamel Siemens Gray colour paint. 4. The edges of doors and shelves should be properly bent to U Shape neatly and finished.	NO	5.00	5.00	1/22/2022
16	23	Hospital Surroundings Dust Bins: RC Ventures Plastic Wheeled Dust Bin for Outdoor Usage/Application, Outdoor, Brand RC Ventures, Material Plastic, Capacity 120 Liters, Number Of Wheels 2	NO	6.00	6.00	2/14/2022
17	25	Stretcher: 1. Overall Size: Length 84", Width 24", Height 32" 2. Design Removeable stretcher top made up of S.S. 20 SWG 304 Grade with full polish with removable cushion made up of 2" foam with inner cloth cover and S.T. quality Green Drill back rexine. 3. The top should be dished to a depth of not less than 1" not more than 2", further fixed on 1" diameter 18 SWG S.S. tubular frames. 4 legs, of 1" diameter 18 SWG supporting floor studs also to be provided, at the bottom of stretcher with nylon shoes. 1, 1/4" Sq, 16 SWG ERW pipes used for vertical and horizontal supporting frame of stretcher. Stretcher handle S.S. 18 SWG 304 grade round shape with full polish, 6" diameter 4 nos. swivelling castor rubber wheels 4. Should have suitable stand for B-Type oxygen cylinder. 5. Epoxy powder coating in seamen's grey colour with minimum 50 microns. 6. Should be ISI / CE Certified.	NO	5.00	5.00	2/1/2022
18	26	Wheel Chair: 1. Floor to seat height 650 mm to 720 mm. 2. Overall Size Width: 1000 mm to 1100 mm, Length 910 mm to 950 mm, Height 480 mm to 510 mm. 3. Design: 1" Diameter 16 SWG ERW tubular frame fitted with metal seat and back. Adjustable horizontal aluminium foot rest 90° - 120° with tread flats. Half round Wooden Hand rest with 1" cushion. Solid rubber tyre wheels 24" x 1 W" fitted with self-propelling hoops and brake arrangement. Full length axle should be provided to fix the rickshaw wheel.	NO	5.00	5.00	2/1/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
19	27	Cardiac Monitors Adult (10) /Paediatric(3): 1.Should have the facility of monitoring ECG, RR, SpO2, NIBP and Dual Temp, for Adult, Pediatric & Neonatal applications. 2. Should have integrated colour display of atleast 12' or more LCD touch screen display. 3.Should have non-volatile Graphical & Tabular trend 4. Should operate independently on both mains and battery. Battery backup for at least 60 Minutes built in battery which is rechargeable.facility for at least 30 hrs.5.Should have alarm limits with alarm levels and alarm indication (visual as well as audio). 6. 3/5 lead ECG measurement, Respiration and simultaneous monitoring of two temperatures 7. Unit should be supplied with following accessories:8.3 lead ECG cable w 12. Pulse Oximeter probe: Reusable Adult and Pediatrics. – Two each with disposable electrodes. 9. 100 no of disposable electrodes, 10. NIBP CUFF – Adult & Pediatric- Two sets each, 11. Temp probe Tape on skin, 13. Monitor should have built in Electro Surgical Unit & Defibrillator protection. 14. Must be ISO/CE / FDA approved.	NO	13.00	13.00	2/1/2022
20	28	Finger Pulse Oxymeter Adult /New Born:a. SpO2 measurement range at least 40-70 and 70 to 99 %, minimum gradation 1%.b. Accuracy of SpO2 better than} 1% for range 40-70 and better than} 3% for range 70-99.c. Pulse rate range at least 30 to 240 bpm, minimum gradation 1 bpm.d. Accuracy of pulse rate better than 5 bpm.e. Signal strength or quality to be visually displayed.f. Audio-visual alarms required: high and low SpO2 and pulse rate (operator variable settings), sensor disconnected, sensor failure, low battery.g. TFT Screen.h. Plethysmograph (may be in form of bar) display is mandatory.2. Settings should have minimum 24 hrs trend memory for SpO2 & PR.3. User's interface Easily accessible touch button to operate the machine.	NO	20.00	20.00	2/16/2022
21	29	Double Surface Phototherapy Unit (Laser): 1. Phototherapy should be based on advanced LED technology, 2. It should have sufficient LED so that the irradiance should cover the entire treatment area, 3. Should have a height adjustable mechanism, treatment distance to the range of 25 to 45 cms should be possible. 4. Wave length of LED should be in the range of 420 –470 nm and irradiance level should be higher than normal blue tube lights. 5. The unit should provide a minimum of irradiance 10Watts/m2. 6. Lamp source should be continuous tiltable to ±90-degree angle to cover the entire treatment area. 7.System should be height adjustable with built in non resettable timer 8.Should work with input 200 to 240Vac 50 Hz supply. 9. Should have safety certificate from a competent authority CE / FDA (US)/ISI	NO	2.00	2.00	2/1/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
22	30	Electric Suction Apparatus, 1HP (3) /1/2 (6)HP new Born: 1. Should be a complete stainless-steel body / any non-corrosive material 2. Should have pump air flow rate minimum 30 – 40/min. 3. Should have vacuum above – 500 mm hg4. Should have three step vacuum adjustments – high, medium and low. 5. Should have secretion container of 2ltr capacity. 6. The hose connection between the suction system and secretion jar should be less than 15 cms. 7. Should have hygienic bacterial filter with overflow protection. 8. Should have sound level maximum of 55 to 65 db. 9. Should have motor capacity of minimum of 0.5 HP (1/2 HP) working power of 220/230 V single phase. 10. Should have power supply indicator, suction on indicator, Unit on/off 5amps DP switch, protector fuse and minimum chord length of 5M with 5 Amps 3 pin top. 11Should be mounted on easy moving castor wheels.	NO	9.00	9.00	2/14/2022
23	31	Electrical Cautery Machine: Monopolar cut: max 400W. Low, Pure, Blend & Endo, ii. Monopolar coag: 120W. Desiccate, Fulgurate & Spray , iii. Bipolar coag: 120W. Macro, Standard and Precise, iv. Bipolar Cut: 100W, v. Vessel Seal: L-5, 150W, Auto-stop & regasp indicators, vi. Programmable power settings: 10 programs, vii. Tissue sensing technology viii. Patient plate contact quality monitoring, ix. HF leakage monitoring, Accessories , Silicon Split Patient Plate * Cable for Patient Plate *Disposable handswitch, 3 Pin *Electrode set *Bipolar forcep * Bipolar cable *5mm laparoscopic vessel ealing instrument with cable *Open biclamp with cable *Three-pedal Footswitch	NO	2.00	2.00	2/14/2022
24	34	Otoscope Welch Allyn: 1. Should be a convenient pocket type otoscope. 2. Should be provided with a halogen light source. 3. Should be able to detach the otoscope head. 4. Should provide no reflections and obstructions. 5. Should provide detachable accessories of various sizes. 6. Should have in built rechargeable battery. Recharge should be possible with direct mains supply	NO	1.00	1.00	2/14/2022
25	35	Oxygen Flow meter with Regulator: 1. Internal reseating relief valve protects against over-pressurization 2. Sintered filter for additional safety and to extend regulator life 3. 2in Diameter gauge 4. 15LPM Oxygen models provide 85 to 90LPM flood maximum, 5. 7LPM models restricted to 10LPM maximum	NO	12.00	12.00	12/30/2021

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
26	36	ECG MACHINE :1. Simultaneous 12 Channel ECG recording with 12 lead simultaneous acquisition 2.Should have visual alarm for open lead, 3.Should have a digital display of 12 channel ECG, 4.QWERTY Alphanumeric keyboard, 5. Built-in ECG Parameters measurements and Interpretation, 6. Minimum 40 ECG Storage inbuilt memory, 7. 3 Operating modes: Automatic, Manual and Rhythm, 8. Should have a maintenance free digital thermal array printer 9. Printer should work with standard thermal paper (should be available in Local Market), 10. Should have 12 lead ECG preview display before taking printouts and should have printer on/off selection, 11.Should have ECG lead annotation facility, 12. Machine should have sufficient battery backup for taking at least 25 nos ECG on a fully charged battery, 13.Should supplied with 2 patient cable sets, 8 clips on electrodes, 12 chest electrodes with silicone rubber bulb, 12 packets of recording paper,1 bottle of jelly and 12 nos. reusable button type electrode, 14. Should operate on mains(220v-50Hz) and rechargeable battery, 15.Recording speed should be 25 mm/ sec and 50 mm/ sec.16. Should have defibrillation protection, 17.CMRR should be>90dB or ECG machine should have digital processing with at least 7000 samples per second from each lead wire. 18. Frequency response 0.05 Hz to 150 Hz. 19. Should have a digital filter for AC and EMG. 20. Should have safety certificate from a competent authority CE / FDA (US) / ISI	NO	6.00	6.00	2/16/2022
27	37	Debrillator Adult (3) And Peadatric (1): 1. Technical characteristics (specific to this type of device):a. Unit should be lightweight compact and portable.b. Unit should have facility for Automatic External Defibrillation and manual defibrillation.c. Should be able to deliver shock from 50-200 joules in biphasic mode via metal chest pads.d. Should having design protection to avoid passage of current to the user.e. The whole system should have an inbuilt recorder; TELEMETRY NOTRECOMMENDED. 2. Settings: Manual AND Automatic. 3. User's interface: The monitor should have a TFT colour display with a three-channel display. 4. Software and/or standard of communication (where ever required): Inbuilt 5. adjustable heart rate alarm as well as paddles & ECG cable disconnection alarms. 6. Power Requirements: 220 to 240V, 50 Hz. 7. Battery operated: Rechargeable battery backup of approximately 5 hours. 8. Protection: Electrical protection by resettable over current breakers or replaceable fuses, Fitted in both live and neutral lines. 9. Power consumption: Should not be more than 160 W. 10. Should be FDA/ CE / BIS approved product.	NO	4.00	4.00	2/16/2022
28	42	NST Machine with probe :1. It should have Numerical display of FHR, TOCO & Foetal Movements Counts, 2. It should have min of 15cm Display for displaying Wave forms of FHR & TOCO, 3. It should have Automatic Foetal Movement Detection, 4. It should have minimum of 2 Hours Battery Backup, 5. It should be provided with Computer Foetal monitoring Software and Data cable for storage & Reload, 6. It should be easy to use & take print out, 7. It should have inbuilt Thermal recorder, 8. It should have inbuilt memory of 10 Hrs Graphical Recording, 9. It should be provided with Aluminium cart with wheels for easy Movement of the machine, 10. It should have built in Network Capability, 11. Should be BIS / CE / FDA certified product	NO	2.00	2.00	2/1/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
29	43	Foetal Doppler : 1. Alarm alert to indicate baby cardiac and tachycardia, 2. Dry nickel cadmium battery with charger, 3. Spiral cable for the probe with length of 1 mtr. Life for battery of at least 6 to 8 hours. 4. volume mode adjustable, 5. Pouch for the machine., 6. Digital display of FHR, 7. Should be ISI/CE/FDA certified	NO	2.00	2.00	2/14/2022
30	44	Infusion Pump :1. Should be operated on drip rate Peristaltic finger pump method.2. Should compatible with most of the IV set (macro/micro drip sets).3. Should have the following flow rates.4. IV Set ml/hr drops/min15 drops/ml 3~450ml/hr 1~100drops/min20drops/ml 3~450ml/hr 1~100drops/min60drops/ml 1~100ml/hr 1~100drops/min5. Should have a flow rate accuracy of $\pm 10\%$ and drip rate accuracy of $\pm 2\%$.6. Should have a volume infused display from 0 to 999.9ml.7. Should have a purge andKVO facility.8. Should have an audible and visual alarm for occlusion pressure, air alarm, door open,empty, low battery.9. Should have a LCD display with backlight and graphical display of infusion Shouldhave a minimum 2hr battery back up at highest delivery rate.10. Should work with input 200 to 240Vac 50 Hz supply.11. Should have safety certificate from a competent authority CE / FDA (US) / ISI.	NO	10.00	10.00	2/1/2022
31	45	Geyser:V-guard geyser 25 litre price 5 star	NO	5.00	5.00	1/11/2022
32	46	Double Door Refrigerator 810 Litres:Samsung refrigerator double door 700 ltr	NO	2.00	2.00	2/15/2022
33	47	Single Door Refrigerator 165 Litres:LG refrigerator single door 180 ltr	NO	2.00	2.00	1/11/2022
34	48	Single Door Mini Refrigerator Litres:LG refrigerator mini	NO	4.00	4.00	1/11/2022
35	49	Split A.C :INSTALLATION CHARGES+Hitachi 1.5tr tr Split Ac 5-Star	NO	10.00	10.00	1/11/2022
36	50	Microave :LG 28 L Convection Microwave Oven	NO	2.00	2.00	1/11/2022
37	51	Stove (Electrical):Electrical stove	NO	3.00	3.00	1/11/2022
38	52	Colour Foetal Doppler:Foetal Doppler, 1. Alarm alert to indicate baby cardiac and tachycardia. 2. Dry nickel cadmium battery with charger. 3. Spiral cable for the probe with length of 1 mtr. Life for battery of at least 6 to 8 hours. 4. Volume mode adjustable. 5. Pouch for the machine. 6. Digital display of FHR. 7. Should be ISI/CE/FDA certified+	NO	2.00	2.00	2/14/2022
39	54	Autoclave Steel Bins 18"x18"	NO	10.00	2.00	12/30/2021
40	55	Autoclave Steel Bins 15"x15"	NO	10.00	2.00	12/30/2021
41	56	Bedside Lockers:Bed Side Locker, 1. Size: H32" x W16" x D16", 2. Size of the Cupboard: H16" x W14"x D16" located in the centre, 3. Cupboard made of CRCA steel sheet with double hinged door and locker facility, 4. Locker top to have S.S. Sheet super imposed with raised edges on three sides, 5. Framework of 1" square M.S. and legs with rubber feet. Full frame and cupboard to be powder coated in Seamen's Grey colour with 50 microns coating., 6. Should be ISI / CE Certified	NO	60.00	15.00	2/1/2022
42	59	Foot End Elevators:Size 78Lx36Wx24H, Back Rest & Knee rest by Screw rod Mechanism, Powder coated Uniformly perforated four sectional CRCA sheet top, Frame work made of Rectangular M.S. Tube, ABS Bow, Collaociable side Railings The above product should conform to applicable ISI Standards in respect of materials, welding process, tests and performance, Finish: Pretreated and Epoxy Powder Coated to be supplied along with Matterss 3' coir n 1" foam	NO	10.00	10.00	2/2/2022
43	60	Plastic Bed Pans	NO	20.00	20.00	2/10/2022
44	61	Plastic Urine Can	NO	20.00	20.00	2/8/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
45	71	Hadson's Tooth Forceps :Length: 4.75" (12cm), b. Handle: Flat, Serrated Thumb, c. Curvature: Straight d. Jaw Style: Fine, e. Tip Configuration: 1x2 Teeth, Side-Grasping, f. Instrument Type: Tissue Forceps g. Material: Surgical Stainless Steel, h. Usage: Reusable, Non-Sterile	NO	3.00	3.00	2/8/2022
46	72	Hadson's non Tooth Forceps :Length: 4.75" (12cm), b. Handle: Flat, Serrated Thumb, c. Curvature: Straight d. Jaw Style: Fine, e. Instrument Type: Tissue Forceps f. Material: Surgical Stainless Steel, g. Usage: Reusable, Non-Sterile	NO	3.00	3.00	2/8/2022
47	73	Periosteum Elevator Size 5 & 6 each size (1 +1): Length: 5" & 6", b. Handle: Flat and Smooth c. Curvature: Straight, d. Jaw Style: Fine e. Tip Configuration: CVD Tip, f. Instrument Type: Surgical Elevator, g. Material: Surgical Stainless Steel h. Usage: Reusable, Non-Sterile	NO	2.00	2.00	2/8/2022
48	77	Copper Handed Curved ARTERY Medium :Curved Artery medium, b. Length: 5-3/4", c. Curvature: Curved, d. Working Surface Style: Serrated, e. Handle: Finger Rings, f. Should be high Quality surgical steel instruments and manufactured from medical grade surgical stainless steel with tungsten carbide, g. Should be Sterilizable	NO	15.00	15.00	2/10/2022
49	80	Dever's Retractor:Size: 12X1 b. Used to retract liver in surgical procedures like cholecystectomy (removal of the gall bladder), vagotomy, c. Should be high Quality surgical steel instruments and manufactured from medical grade surgical stainless steel, d. Should be Sterilizable	NO	5.00	5.00	2/10/2022
50	81	Disecting Forceps Toothed :Made of 410 grade stainless steel, b. Total length – 15 cm, c. Sand blasting from inside, d. Tip should be 2x1 e. Matt/ dull finish,	NO	100.00	100.00	2/10/2022
51	82	Disecting Forceps non Toothed :Made of 410 grade stainless steel, b. Total length – 15 cm c. Sand blasting from inside, d. Tip should be 2x1 e. Matt/ dull finish	NO	100.00	100.00	2/10/2022
52	83	Sponge Holder :Size: 9-1/2" (24.1 cm), Straight, Serrated Jaws, b. Fully graduated in centimetres c. Should be high quality surgical steel Instrument and manufactured from medical grade Surgical stainless steel, d. Should be Sterilizable	NO	70.00	70.00	2/10/2022
53	84	Speculum Medium :Shape: Should be Double Ended b. Size: Should be medium in size (blade one size 75x30mm, other 80x35 mm), c. Material: Should be high Quality Surgical steel instrument and manufactured from medical grade surgical Stainless steel, d. Safety: Protects Patients against Cross infection risks, e. Use: Should be reusable	NO	60.00	60.00	2/10/2022
54	85	Anterior Vaginal wall Retractor:Made of 410 Grade Stainless Steel, b. Total Length – 25.5CM c. Rings should be oval shaped, d. Both sides serrated rings, e. Ring internal diameter – 15MM & 18MM f. Matt/ Dull Finish	NO	13.00	13.00	2/8/2022
55	88	B.P.Handle big:Forgings from Stainless Steel, b. Silk Matte Satin Finish, c. To Hold Scalpel Blades, d. Used Mostly In All Surgery.	NO	30.00	30.00	2/10/2022
56	89	B.P. Handle small:Forgings from Stainless Steel, b. Silk Matte Satin Finish, c. To Hold Scalpel Blades, d. Used Mostly In All Surgery.	NO	10.00	10.00	2/10/2022
57	90	Varicose Veins Stripper	NO	2.00	2.00	2/8/2022
58	91	Ovum Forceps (gynec):Size: 9-1/2" (24.1 cm), Straight, Serrated Jaws, b. Fully graduated in centimetres, c. Should be high quality surgical steel Instrument and manufactured from medical grade Surgical stainless steel, d. Should be Sterilizable	NO	2.00	2.00	2/8/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
59	92	Cord Cutting Scissors: Should be very wide blades with large, rounded, blunt tips that slide past each other b. The blades are attached to handles with the proximal end conformed as a ring to facilitate holding and operating with the fingers; both parts are joined by a swivel pin in the centre. c. Should be high quality surgical steel Instrument and manufactured from medical grade Surgical stainless steel d. Should be Sterilizable	NO	20.00	20.00	2/10/2022
60	93	Episcotmy Scissors: Made of 420 grade stainless steel b. ISI/CE/FDA certified & anti rust instrument, c. Total length – 14 cm, d. Blade length – 4.6 cm, e. Blades should be angled, f. Rings should be smooth g. Matt/ dull finish	NO	25.00	25.00	2/10/2022
61	95	Steel Trays medium : Instrument Tray with cover – Stainless steel of 304 grade, b. Size: 300x 200 x 65mm	NO	60.00	60.00	2/10/2022
62	96	Cheattle Forceps: Made of 410 grade stainless steel b. ISI/CE/FDA certified & anti rust instrument c. Total length – 25.5 cm, d. Jaw length – 7.8 cm e. Jaws should be smooth without serration f. Rings should be smooth, g. Matt/ dull finish	NO	20.00	20.00	2/10/2022
63	97	Suction Tips Different Size: Tubing Material: Medical-grade Polyvinyl Chloride (PVC) Plastic, b. tubing size 1/4", length 1.80m, Yankauer handle with control vent and crown tip, c. tubing size 1/4", length 3.60m, ankauer handle with control vent and crown tip d. tubing size 3/16", length 1.80m, Yankauer handle with control vent and crown tip, e. tubing size 3/16", length 3.60m, Yankauer handle with control vent and crown tip	NO	10.00	10.00	2/8/2022
64	98	Laryngo Scope with Blades ADULT: Handle: stainless steel or chromium-plated, slightly rigged, b. Depressor and laryngoscope blade: stainless steel, curved or straight. c. Complete, ready-to-use, the laryngoscope should be L-shaped so that the handle and batteries are at a right angle to the blade. d. Illumination: battery compartment in the handle, lamp positioned on the blade. e. An instrument used to inspect the larynx, comprised of a:- Hollow handle, 2-battery compartment type. - Spatula or blade: f. Macintosh type: slightly curved blade with a small bulbous tip, fixed to a hook-on handle. g. Each blade has a single bulb, removable for cleaning.	NO	21.00	2.00	12/30/2021
65	99	Laryngo Scope with Blades Peadeatric: Handle: stainless steel or chromium-plated, slightly rigged. b. Depressor and laryngoscope blade: stainless steel, curved or straight. c. Complete, ready-to-use, the laryngoscope should be L-shaped so that the handle and batteries are at a right angle to the blade. d. Illumination: battery compartment in the handle, lamp positioned on the blade. e. An instrument used to inspect the larynx, comprised of a: - Hollow handle, 2-battery compartment type. - Spatula or blade: f. Macintosh type: slightly curved blade with a small bulbous tip, fixed to a hook-on handle. g. Each blade has a single bulb, removable for cleaning.	NO	11.00	5.00	12/30/2021
66	100	Ambu bag Adult /Peadtric Set (10 +10): 700ml and 200ml Self inflating double ended silicone bag with mounts, b. Side feed oxygen inlet, C. Type "L" non-rebreathing valve with pressure limiting device 40cms of water, d. Size 0A Circular Pedi All Silicone facemask, e. Reservoir Hose with Adaptor to provide higher oxygen & 1.5mtrs oxygen enrichment tubing f. Carrying case,	NO	20.00	18.00	2/8/2022
67	101	New Born Ambu Bag: Stroke volumes: 150 ml b. Patients weight: < 10 kg (1 year), c. Total bag volume: 220 ml, d. Oxygen reservoir volume: 100 ml	NO	10.00	10.00	2/10/2022
68	102	Spot Light	NO	10.00	10.00	2/16/2022
69	105	Shrodhkar Forceps	NO	1.00	1.00	2/10/2022

SL No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
70	108	Huntley's Knife	NO	1.00	1.00	2/8/2022
71	111	Ear Hooks & retractor	NO	1.00	1.00	2/8/2022
72	112	Retractor	NO	1.00	1.00	2/8/2022
73	117	Circlet Reduction Clamp large	NO	1.00	1.00	2/8/2022
74	118	Circlet Reduction Clamp small	NO	1.00	1.00	2/8/2022
75	119	wire Cutter	NO	1.00	1.00	2/8/2022
76	120	Hand Drill	NO	1.00	1.00	2/8/2022
77	121	Stainless Pins (ORTHO)	NO	1.00	1.00	2/8/2022
78	122	Sinus probe	NO	1.00	1.00	2/8/2022
79	123	Towel Clip	NO	1.00	1.00	2/8/2022
80	124	S.S. WIRE different Sizes (ORTHO) EACH Size	NO	1.00	1.00	2/8/2022
81	125	K WIRE DIFFERENT EACH SIZES (ORTHO)	NO	1.00	1.00	2/8/2022
82	128	Super micro ear Forceps oval Cupped jaws 0.8 x 1.0mm Effective Length 75mm	NO	1.00	1.00	2/8/2022
83	130	Super Micro Ear Forceps oval Cupped jaws 0.6x 0.8mm Effective Length 75mm	NO	1.00	1.00	2/8/2022
84	131	Hertman Ear Forceps serrated OPEN -CLOSED TIP Type	NO	1.00	1.00	2/8/2022
85	132	Shear ear Forceps, Scissors, Straight, Blade Length 6.0mm Effective Length 75mm	NO	1.00	1.00	2/10/2022
86	133	Volkman Retractor, 3 PRONGS blunt	NO	1.00	1.00	2/8/2022
87	134	Scissors, CURVED LENGTH 115MM	NO	1.00	1.00	2/8/2022
88	135	Tissue Forceps, HOOK, TIP, WIDTH 0.6MM, LENGTH 130 MM	NO	1.00	1.00	2/8/2022
89	136	Pick, Small, right, length 180mm	NO	1.00	1.00	2/8/2022
90	137	Lempert ear Speculum, for Inner Ear, nasal speculum type	NO	1.00	1.00	2/8/2022
91	138	Dissecting Forceps, FOR Surgical, Hook, Tip, Width 1.5mm Length 130mm	NO	1.00	1.00	2/8/2022
92	139	Scissors, Straight, Length 115 mm	NO	1.00	1.00	2/8/2022
93	140	Pick, Small, left, length 180mm	NO	1.00	1.00	2/8/2022
94	141	Sickle Knife For STAPEDIUS MUSCLE	NO	1.00	1.00	2/8/2022
95	142	round knife, straight, Diameter 2.5mm	NO	1.00	1.00	2/8/2022
96	143	Pick, MEDIUM, RIGHT, LENGTH 180MM	NO	1.00	1.00	2/8/2022
97	144	Pick, Small, Right, Length 180mm	NO	1.00	1.00	2/8/2022
98	145	Rosen Probe 90 DEGREE, Tip Length 0.6mm	NO	1.00	1.00	2/8/2022
99	146	Rosen Probe 90 DEGREE, Tip Length 1mm	NO	1.00	1.00	2/8/2022
100	150	Lucas ear Forceps, no hook	NO	1.00	1.00	2/8/2022
101	151	Myringotomy Knife	NO	1.00	1.00	2/8/2022
102	152	Shah's Ear Grommet	NO	1.00	1.00	2/8/2022
103	153	Mollison's MASTOID Retractor	NO	1.00	1.00	2/8/2022
104	156	Lempert's Endural Speculum	NO	1.00	1.00	2/8/2022
105	159	Crocodile Forceps	NO	1.00	1.00	2/8/2022
106	161	Solar water - 500 lpd ETC SWH (PC) 58 dia	NO	1.00	1.00	2/8/2022
107	183	High Definition Projector: Projector WXGA, 3600 Lumens	NO	4.00	4.00	2/10/2022
108	184	Tripod For Projector - Ceiling Mount	NO	2.00	2.00	1/8/2022
109	185	Tripod For Screen: Logic 7x5 pull down screen,	NO	2.00	2.00	2/14/2022
110	188	Computer: High Configuration, 2TB Ram, Generation Core i 7/i 9, 3HP EliteDesk 800 G4 MT i7-8700-8GB DDR4 RAM, AMD Radeon R7 430 2GB Gfx Dedicated 2TB HDD with 7200 RPM, DOS, DVD RW, 18.5" TFT, 3 year on site warranty	NO	25.00	25.00	2/14/2022
111	189	Jumbo Jet xerox Machine (1 COLOURED)-HP LASERJET 1136 MFP PRINTER -ALL-IN -ONE Print, scan, copy	NO	2.00	2.00	1/11/2022
112	190	Printer with Scanner (COLOURED) (A4)-Speed: 25 PPM (Network Printing, Copying, Scanning & Wifi) A4 Size -Pass 600x600 DPI Document Feeder Scan to mail, Scan to folder (UFR II Fast Rendering II Direct Print From USB Pen Drive	NO	25.00	25.00	1/11/2022
113	192	Pen Drive 128 GB-SANDISC 128 gb pen drive	NO	10.00	10.00	1/11/2022
114	193	Hard Disc 1TB-Sagate HDD 1 TB EXTERNAL Back up hdd	NO	10.00	10.00	1/11/2022
115	194	32" Colour Television-32" TV Panasonic	NO	5.00	3.00	1/11/2022
116	195	online UPS FOR COMPUTERS ALL COMPUTERS	NO	25.00	25.00	1/11/2022
117	196	Computers Accessories (wire less key board, Mouse)-HP Wireless KB & MOUSE	NO	20.00	20.00	1/11/2022

Sl. No	Item no	Description of work	Unit	Approved tender Qty	Quantity of Material received	Material received on (Date)
118	197	Lap Top-HP i5-8250U, 4GB DDR4 RAM, 1TB SATA14" LED HD, No DVDRW, 1 Yr Onsite Warranty with 1Yr ADP, With Bag	NO	2.00	2.00	1/11/2022
119	199	labomed binocular microscope with UPS BACK UP (180-250V /ac):Viewing Body: Bino/Trino Butterfly style Adjustable height 30deg, incline, 360 rotatable Single Mould stand with Extended base for hand rest. Reverse quadruple nose piece. Ultra Smooth Cam technology Co-axial controls Coarse & Fine focus knob. RACKLESS Double plate stage with Co-axial control for x/y movement of slide, DOUBLE Slide holder.Illumination: 6v-20w HALOGEN bulb OR LED with built-in battery Back of approx. 2 Hrs, with intensity control, the system allows flate field image and superb contrast in expanded 20mm field of view.Obj.: infinity PLAN Ach. 4x,10x,40, (SL), 100x(SL) Oil Imm. Eye Piece : WF 10x (FOV 20), Focusable with eye guards.	NO	1.00	1.00	2/1/2022
120	203	X-RAY viewing Box :Power Consumption: 14 W Light Source: LED Light Emitting Diodes Power Supply Input: AC100-240V 50/60Hz Application: Clinical, Hospital Net weight: 3 Kg Thickness: 45 mm	NO	6.00	6.00	2/14/2022

Here by declared that the above mentioned quantity of materials from serial number 01 to 120 are taken over by me for our Government Hospital with perticular dates in working condition with good Quality.

Date
Place : Yelahanka, Bangalore



Santhosh D

SANTHOSH.D.

Contractor PWD Class-1, Civil Contractor
Reg No. CBS/12734/Civil/2010
Sahakamagar, Bangalore-560092

Taken Over by me

Asma Tabassum
Dr. ASMA TABASSUM

MBBS., DDVL
KMC Reg No. 30591
Skin Specialist/Administrative Medical Officer
General Hospital
Yelahanka, Bangalore (U) Dist

Handed over by me
2/2/22

Handed over by me